

QUICK•STEP® Seal&Click

LAMINATE



Product description

Quick-Step® Seal&Click has been especially designed to provide prolonged protection for Quick-Step® Lagune against damp when used in bathrooms and kitchens.

- Contents: 125 ml (+/- 26m² when applied to the short end of Quick-Step® Lagune)
- Packaging quantity: 10

Applications

Only to be used with Quick-Step® Lagune floor when laid in bathrooms or kitchens. Quick-Step® does not guarantee optimum protection when used with other Quick-Step® floors or with other brands of laminate floors.

Characteristics

If Quick-Step® Seal&Click is applied correctly, the following characteristics are guaranteed:

- √ Protection against damp
Quick-Step® Seal&Click provides permanent protection against damp that penetrates into the joints from above.
- √ Filling capacity
Quick-Step® Seal&Click has a high filling capacity, which means damp cannot penetrate between the tongue and groove joint.

In addition, Quick-Step® Seal&Click spreads evenly in the joint to guarantee protection across its full length.

√ Elastic

Wood is the main component of your Quick-Step® Lagune floor. Wood expands and contracts when it is subject to temperature and humidity variations. Thanks to its permanent elasticity, Quick-Step® Seal&Click maintains its valuable characteristics under all conditions.

√ Does not stick

Quick-Step® Lagune floor with its Uniclic® system can be easily removed from one room for use in another. Use Quick-Step® Seal&Click to ensure that you can continue to enjoy this benefit. Quick-Step® Seal&Click is not glue, so this product can be removed again completely.



√ Easy to use

Quick-Step® Seal&Click can be easily applied in the correct manner.

√ Your floor is just as easy to clean

Your Quick-Step® Lagune floor laid with Quick-Step® Seal&Click does not have to be cleaned any differently than a floor laid without joint-sealing product.

Tip: Use the Quick-Step® maintenance kit for the fast and professional cleaning of your floor (QSCLEANINGKIT).



√ Fast processing

√ Transparent

Quick-Step® Seal&Click is transparent, which means it won't damage your quality floor and won't leave visible joints.

Instructions

√ Apply Quick-Step® Seal&Click generously along the top edge of the groove on the short side.

Only apply to the short side of the Quick-Step® Lagune plank. It is not recommended to use the joint-sealing product under the rubber strip. The rubber strip already optimally protects the long side against damp.

√ The surface must be clean, dry, dust and grease-free.

√ Before joining the planks, apply Quick-Step® Seal&Click to the groove of the short side.

Apply sufficient product so that it appears at the top of the joint when you click the planks together.

√ Apply Quick-Step® Seal&Click in a single movement and without interruption.

- √ Click the planks together immediately after applying Quick-Step® Seal&Click (before the product begins to dry). Follow the installation instructions for your floor.
- √ It is recommended to wait 10 to 20 mins before removing the excess product.
- √ Wipe the excess product off with a dry cloth or remove first with a plastic spatula and then wipe with a dry cloth.

Tip: Excess product can be removed most easily when completely dry.

- √ Can support a light load after about 1 hour, and can be walked on after 24 hours.
- √ The room where the product is applied must be adequately ventilated.
- √ Remove Quick-Step® Seal&Click each time you disassemble the planks for installation in another room.
- √ Always close the tube tightly (even during use) in order to prevent the product from drying out.

Storage life

Minimum 18 months after production date (see batch code).

Consumption

plank size [cm]	estimated area sealed with one bottle 500ml [m2]	estimated area sealed with one tube 125ml [m2]
120 x 19	32	8
120 x 12,34	22	6
205 x 20,5	37	9
122,4 x 40,8	62	16
138 x 15,6	27	7
138 x 19	32	8
62,4 x 62,4	62	16